Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R

1.5 kVA Explosion Proof Isolation Transformer - 220 V Primary - 110 V Secondary - ATEX Zone 2, 1PH/N3R - 50 Hz

Product ID: 342505



Image: MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-EXP-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R Explosion Proof Isolation Transformer

Phase: Single Phase

Frequency: 50 Hz
kVA: 1.5
Primary Voltage: 220 V
Taps: TBD
Secondary Voltage: 110 V
Amps: 10A
Winding Material: Copper
Insulation: 180°C
Temperature Rise: 115°C
Impedance (Std): -
Seismic: Yes
Reverse Connectible: Yes
Electrostatic Shield: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: Wire Leads
Secondary Termination: Wire Leads
Operating Temperature: 50C to 60C
Enclosure Material: NEMA Type 3R Non-sparking
Finish: -
Dimensions: 11.75"H x 7.00"W x 6.50"D
Weight: 47 lb
Mounting: Floor Mount

Ratings

NRTL Listed for United States, Canada and International Locations
ATEX Zone 2
ANN Cooling
IP65 Rated (Outside Installations)
Explosion Proof Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R 220 V 1 Phase Explosion Proof Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 1.5 kVA, the MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R isolation transformer is a single phase unit with a primary voltage of 220 V. It also provides a secondary voltage of 110 V. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. The transformer is designed for ATEX Zone 2 rated work sites.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP65 for outside installations.

Benefits: The MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R explosion proof isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ATEX-DOE16-1P-220V-1.5KVA-110V-50HZ-N3R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our

prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs