

EXP-RT-DPST-MIN.30-12VDC-M1

Explosion Proof Timer Switch - Class I, II, III - 30-Minute Timer, DPST Switch - NEMA - 12V DC

Product ID: 343979



Image: EXP-RT-DPST-MIN.30-12VDC-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-RT-DPST-MIN.30-12VDC-M1 Explosion Proof Timer Switch

Unit Type: Explosion Proof Timer Switch
Dimensions: 5.09" x 3.5"x 3.06"
Minutes: 30 Minutes
Configuration: DPST
Voltage: 12 VDC
Amperage: 20A @ 12 VDC
Horsepower: N/A
Ambient Operating Temp: -40 °F to 104 °F (-40 °C to 40 °C)
Unit Materials: Copper-free Cast Aluminum
Mounting: External Mounting Lugs on Body
Hub Quantity: (2) Feed Through or (1) Dead End
Hub Size: 1/2" or 3/4"

Ratings/Approvals

Class I Div 1&2 Groups C & D
Class II Div 1&2 Groups E,F,G
Class III, Div 1&2
NEMA 3,7(BCD),9(EFG),12

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

Made in Texas

The Larson Electronics EXP-RT-DPST-MIN.30-12VDC-M1 Explosion Proof Timer Switch provides timed control for equipment in combustible work sites and hazardous locations. The 30-minute timer is configured with a DPST switch for reliable control of connected equipment. Constructed of copper-free cast aluminum, the unit is NEMA-rated for durability in rugged environments and is rated for 12 VDC operation.

The EXP-RT-DPST-MIN.30-12VDC-M1 offers robust timing control of equipment in hazardous

environments. This unit is equipped with a double-pole single-throw (DPST) switch, allowing operators to control equipment for up to 30 minutes. The explosion proof timer switch is designed for Class I, Division 1 and 2; Class II, Division 1 and 2; and Class III environments and operates at 12 VDC with a 20A rating.

The EXP-RT-DPST-MIN.30-12VDC-M1 is constructed of copper-free cast aluminum for superior performance and durability. These switches are not factory sealed and require external sealing fittings. Two external mounting lugs provide simple and secure mounting of the unit to walls and flat surfaces. This explosion proof unit is available with either 1/2" or 3/4" NPT tapped hubs. The conduit openings are provided on the top and bottom of the unit in feed-through versions, while dead-end versions have a single conduit hub, providing easy and secure connection to the main power supply. The unit operates in ambient temperatures from -40 °F to 104 °F (-40 °C to 40 °C).

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Lighting, Wet areas or Locations Where Combustible Dust is Present. This switch can be used with fans, motors, heaters, and lighting (including incandescent, halogen, compact fluorescent, tungsten, and LED lighting loads).

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs