Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

1.25 MVA Pad Mount Transformer - 20000V Delta Primary, 400Y/230 Wye-N Secondary - Copper, ONAN/Future ONAF, Bell Green, NEMA 4X, Stainless Steel

Product ID: 343983



Image: MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1 Pad Mount Transformer

Transformer Type: Pad Mounted, Compartmental-Type
Transformer Configuration: Liquid Filled Pad Mounted
Transformer Feed Type: Loop Feed
Operation: Step-Down Operation (Not Approved for Step-Up)
Phase: Three Phase
Capacity: 1.25 MVA
Vector Group: Dyn1
Primary Voltage: 20000V
Primary Voltage Switch: N/A
Primary Voltage Class: 25 kV Class
Primary Phasor: Delta
Primary BIL: 95 KV
Secondary Voltage: 400Y/230
Secondary Voltage Class: 1.2 kV Class
Secondary Phasor: Wye-N
Secondary BIL: 30 KV
Frequency: 60 Hz
Temperature Rise: 65°C
Insulation Rating: Class E Insulation - 120°C, 248°F
Cooling Class: ONAN; Self-Cooled
Forced Air (Fans): None, Provisions Only
Tap Changer: 5-position De-energized Tap Changer
Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps
Tap %: 2.5%

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.29
Complies with ANSI / IEEE C57 12.34
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.110
Complies with ANSI / IEEE C57.12.131
Complies with ANSI / IEEE C62.11
Complies with ANSI / IEEE C62.22
Complies with ANSI / IEEE 386
Complies with ANSI / IEEE C2
Complies with ANSI / IEEE C37.47
Complies with ANSI Z535.4
Complies with ASTM D3487
Complies with ASTM D6871
Complies with NEMA 260-1996
Complies with 10 CFR Part 431
Complies with CSA C2.1-06
Complies with CSA C50
Complies with CSA C88
Complies with CSA C88.1

Tap Changer Switch Rating: 200-Amp, 25 kV
Tap Changer Switch Location: High Voltage (HV) [Left Side] Front Compartment
Impedance: 5.0-7.5% Typical
Primary Connection Type: Dead Front
Primary Termination Arrangement: V Terminal Arrangement
Primary Termination: Universal Well Bushings w/ Removable Studs, 200A Load Break Elbows w/ Inserts
Primary Connection Qty: (6) Primary Connections for use w/ Elbow Connectors
Primary Parking Stand Qty: (6) Welded Brackets for Installing Accessory Parking Stand Bushings
Primary Bushing Rating: 25 kV Class, 125 kV BIL, 200A, Load Break, IEEE 386 Color Red
Primary Neutral Connection: N/A
Primary Surge Arrestors: Included, (3) High Voltage Elbow Surge Arrestors
Primary Surge Arrestor Voltage Rating: 21 kV Class Elbow Arrestor
Primary Surge Arrestor MCOV Rating: 17 kVrms
Primary Overcurrent Protection (OCP): Bayonet Expulsion Fuses
Primary Overcurrent Protection Method: Fused, Oil-Immersed
Primary Overcurrent Protection Holder: Bayonet Fuse Holder w/ Flapper Valve and External Drip Shield
Primary Grounding Provisions: (2) Grounding Lugs In HV Compartment, Accommodate a 4/0 AWG copper conductor, H-J Enterprises, part number, HJ AS1203-001
Secondary Connection Type: Live Front
Secondary Termination Arrangement: Staggered Terminal Arrangement
Secondary Connections: NEMA Spade Terminals, 6-Hole Spade, Externally Clamped, Accepts up to (6) Double Lug connections with (3) cables per side of Spade connector
Secondary Connection Qty: (4) Externally Clamped One-Piece Epoxy Bushings Copper Threaded Studs
Secondary Connection Supports: N/A
Secondary Over Current Protection (OCP): N/A
Secondary Neutral Connection: Secondary X0 Neutral Grounded to Tank via 1/2”-13 UNC Tapped Hole, 7/16” Deep Bung & Copper Ground Strap
Secondary Grounding Provisions: (1) Grounding Lug In LV Compartment, Accommodate a 4/0 AWG copper conductor, H-J Enterprises, part number, HJ AS1203-001
Metering Current Transformer (CT): N/A
Metering Panel: N/A
Auxiliary Control Panel: Included, 120 Vac control voltage, equipped with local indication and alarm contacts for pressure gauge, temperature gauge, oil level gauge, and pressure relief device
Load Break Switch: 4-Position Load Break Switch
Load Break Switch Qty: (1)
Load Break Switch Rating: 200-Amp, 15 kV
Load Break Switch Location: High Voltage (HV) Front Compartment
Efficiency Standard(s): Meets DOE 2016 Standards, Meets CSA Standards Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Mineral Oil Insulating Fluid, Non-PCB Fluid
Fluid (Oil) Capacity*: 245 Gallons
Fluid (Oil) Weight*: 1,891 lbs
Liquid Level Indicator: Analog Dial Gauge with alarm contacts
Temperature Indicator: Analog Dial Gauge with alarm contacts
Pressure/Vacuum Indicator: Analog Dial Gauge with alarm contacts
Pressure Relief Device: Automatic, 50 SCFM (plus high-volume PRD), each w/ auxiliary alarm contacts
Fault Indicator: N/A
Gas Sampler Valve: Included, Schrader Valve
Fill Valve: 1" NPT Port w/ Removable Bolt Plug
Fill Valve Location: Front Compartment
Drain Valve: 1" NPT Port w/ 5/8" NPT Sampler Valve

Complies with CSA C88-16
Complies with CSA C227.4
Complies with CSA C227.5
Complies with CSA C802-3
Complies with CSA C802.1

Features

Penta-head Bolt Entry Assembly

High-Fire Point Insulating Fluid

Non-PCB Insulating Fluid
Tamper Proof Housing
Hinged Front Compartment Doors, Pad Lockable
NEMA 3R Wiring Compartment
Hot Stick Included, HV Door Mount

Efficiency %: 99.20%

Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 85°C Reference Temp.

No Load Loss (in watts): +/- 1,300W

Full Load Loss (in watts) at 100%: +/- 8,500W

Total Load Loss (in watts) at 100%: +/- 9,800W

Total Losses at 55°C LL Temp. & 20°C NL Temp.

Total Load Loss (in watts) at 50%: +/- 3,221W

Note: *Losses offered are typical only, not guaranteed*

Labeling:

Externally Stencilled (Painted) KVA Rating
Externally Stencilled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

Factory Tests:

Winding Resistance Test
Insulation Resistance Test
Voltage Ratio Error Test
Short-circuit Impedance Test
No-load Loss (Wattage) Test
Load Loss (Wattage) Test
Induced Voltage Withstand Test
Separate Source Voltage Withstand Test
Pressure Integrity Test

Drain Valve Location: LV Compartment
Winding Material: Copper
Ambient Temperature Rating: 40°C
Ambient Operating Temperature Range: -40°C to +40°C (-50°F to +104°F)

Sound Level: 58 dBA, Complies to NEMA TR1

Elevation (Altitude): 3300ft (1000 meters) Above Sea Level
Core Material: Grain Oriented Steel
Tank Material: 304 Stainless Steel
Cabinet Material: 304 Stainless Steel
Base Platform Material: 304 Stainless Steel
Portability: Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
Housing Type: Compartmental Air-Filled Cabinet w/ Locking Doors, HV Compartment Left, LV Compartment Right, Steel Barrier Separation, HV Door Spring-Loaded Release Pin in LV Compartment
Enclosure Rating: NEMA 4X Weatherproof Wiring Cabinet, Sealed Tank
Seismic Rating: Yes
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: Munsell™ 7.0 GY 3.29/1.5 Bell Green
Mounting: Pad Mounted
Conduit Opening: Bottom Feed Underground Entry/Exit
HV Compartment Base Wireway Dimensions*: 20"-W x 5"-D
LV Compartment Base Wireway Dimensions*: 20"-W x 5"-D
MV/LV Compartment Cabinet Depth*: 24"-D
Tank Cover Access Handhole: Included
Dimensions*: 73"-W x 71"-D x 73"-H
Dry Weight (w/o Oil)*: 3,715 lbs
Total Weight (Liquid Filled)*: 8,327 lbs
*Please note that numbers are approximate and subject to change

Shipping:
Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
Note: *Crated shipping in lieu of palletizing can be done upon request for an additional fee*

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1 Industrial Pad Mount Transformer from Larson Electronics offers powerful, reliable and efficient power distribution in indoor, outdoor and public locations. The low operating costs, low heat emissions and low cost of ownership make this transformer ideal for a wide range of applications and businesses. An enclosed design caters to installations on concrete pads without protective fencing.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 1.25 MVA, the industrial transformer features a primary voltage of three-phase 20000V Delta and a secondary voltage of three-phase 400Y/230 Wye-N. The unit has a primary loop feed for daisy chain installations and dead-front primary connections. We also offer systems with radial feed and live front primary connections. This transformer features a 5-position tap changer with two +2.5% taps above and two -2.5% taps below to allow small changes in voltage.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of a rectangular coil and a five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1 is air cooled and does not have fans but has mounting provisions for fans.

Enclosure Design: This pad mounted transformer is a compartmental design. The tank and housing are fabricated from stainless steel. The front electrical enclosure carries a NEMA 4X rating. The high voltage and low voltage compartments are located in front of the transformer tank, with the high voltage compartment on the left side and low voltage compartment on the right side. The HV and LV compartments are air filled and separated by a full length steel barrier between the compartments. A removable steel plate at the base of the HV and LV compartments prevents rodents and other intrusions from entering the enclosure once installed. This steel plate allows for underground conduit entry into the enclosure compartments. Two hinged exterior doors allow for access into the compartments. A single pad lockable handle on the low voltage compartment door allows for securing the transformer. A spring loaded pin within the low voltage compartment prevents the high voltage door from being opened without pulling the safety pin. A hot stick is included in the high voltage compartment, mounted to the HV door.

Temperature Rise: This unit features 65°C temperature rise for reduced heat waste, increased reliability and longer life. At 65°C temperature rise, the transformer offers 1.25 MVA. The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Insulation Fluid: The MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1 features mineral oil cooling fluid (ONAN) with a capacity of 245 gallons. We offer transformers with biodegradable or FR-3 oil fluids, if needed.

Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% loan conditions, which helps preserve the transformer's lifespan and performance.

Gauges: The following gauges are included with the system: liquid level, temperature, and pressure/vacuum gauges. Each gauge is an analog dial type equipped with SPDT auxiliary contacts for remote alarm/trip indication. All gauge contacts are wired to the 120 Vac auxiliary control panel terminal block for monitoring and control integration.

Fault Pressure Devices: This transformer features an automatic action fault pressure device. Fault pressure devices are used to detect high rates of pressure rise within the tank.

Rapid Rise Relay: There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.

Surge arresters: This system comes with high elbow surge arresters on the primary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without high elbow surge arresters that have mounting provisions for customer-provided surge arresters.

Load Break Switch: The transformer is equipped with a 4-position load break switch.

Valves: The MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1 is equipped with a pressure relief valve, fill valve and drain valve with sampler port.

Protection Fuses: This transformer contains bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.

Mount: The heavy-duty enclosure makes the unit suitable for both indoor and outdoor applications. This power distribution system can be pad mounted on concrete pads.

Benefits: The MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1 pad mount transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.


Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, public locations and more.


Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

REV	DESCRIPTION	DATE
A	PRODUCT DESCRIPTION	09/2026


MT-PML-R7-3P-DVP-1.25MVA-YK-LT
-DF-A6-BMP-CS-2B4-M1


LARSON ELECTRONICS®






Rated Capacity	Loss(w)		Dimensions(in)			Weight	
	No-load Loss (W)	On-Load Loss	W	D	H	Oil Capacity (gal)	Total Weight (lbs)
1.25 MVA	1300	8500	73	71	73	245	8327





WIRING CONNECTION



PHASOR DIAGRAM

Remark: Dimensions here are in inches. Only for approval/preliminary design.


No.	Name	Model	Qty.	Material	Remark
23	fans				provision only
22	SS hinges&pins				
21	padlock	penta-head bolt	1		
20	current limiting fuse		3		
19	insulation oil	Mineral oil			
18	gas sample valve		1		Schrader Valve
17	drip shield		1		
16	parking stand		6		
15	nameplate		1		
14	grounding lug		1		
13	drain valve w/ sampler		1		
12	grounding lug	Ø25*20, M10	4		with copper bar
11	reinforcing rib	8mm steel	1		
10	LV bushing		4		6-hole spade
9	HV bushing	200A bushing	6	load break	with (3) arrester
8	off-circuit tap changer		1		
7	load breaker switch		1		4-position
6	temperature indicator		1		
5	oil indicator		1		
4	Bayonet fuse		3		w/ flapper valve
3	oil fill valve		1		
2	pressure relief valve		1		automatic action
1	pressure indicator		1		

LARSON MAGNETICS

9419 E US HWY 175,
KEMP, TX 75143

TITLE
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

DRAWN BY	DATE	REV
	09/2026	A
CHECKED BY	SHEET #	DRAWING #
	1 OF 2	101



THREE PHASE PAD MOUNTED TRANSFORMER
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

High Voltage		
Tap Position	Voltage (V)	Current (A)
1	21013	34.3
2	20500	35.2
3	20000	36.1
4	19500	37.0
5	19013	38.0
Low Voltage		
Voltage (V)		Current (A)
400		1804.3

Rated Capacity	1250	KVA
HV	20000	V
LV	400Y/230	V
Impedance	5.0-7.5	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	Dyn1	
Rated Frequency	60	Hz
Cooling Type	ONAN	

Product Code	343983		
Serial Number			
HV BIL	95	LV BIL	30
Winding Con.	HV:Cu	LV:Cu	
Temp. Rise	65		°C
Oil Capacity	245		GAL
Total Weight	3715		LBS
Body Weight	8327		LBS
Step-Up Operation:	NO		

Tank must be solidly grounded - NON-PCB Oil

Mineral Oil Insulating Fluid

Wire Connection

Phasor Diagram

Maximum operating pressures of liquid preservation system_____kPa (lbf/in2) positive and _____ kPa (lbf/in2) negative.
Tank designed for_____ kPa (lbf/in2) vacuum filling.(insert any portion of the transormer that cannot withstand the stated vacuum level (i.e., conservator, LTC boards, radiator.)
Liquid level below top surface of the highest point of the highest manhole flange at 25 °C_____ mm(in). Liquid level changes _____ mm(in)per 10°C change in liquid temperature.

ANSI C57.12.34-DOE 2016 Compliant-Manufactured 2026.09

LARSON MAGNETICS

Larson Magnetecs LLC

Kemp, TX USA

LARSON MAGNETICS


9419 E US HWY 175,
KEMP, TX 75143


TITLE		
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1		
DRAWN BY	DATE	REV
	09/2026	A
CHECKED BY	SHEET #	DRAWING #
	2 OF 2	102

REV	DESCRIPTION	DATE
A	PRODUCT DESCRIPTION	09/2026


MT-PML-R7-3P-DVP-1.25MVA-YK-LT
-DF-A6-BMP-CS-2B4-M1


LARSON ELECTRONICS®






Rated Capacity	Loss(w)		Dimensions(in)			Weight	
	No-load Loss (W)	On-Load Loss	W	D	H	Oil Capacity (gal)	Total Weight (lbs)
1.25 MVA	1300	8500	73	71	73	245	8327





WIRING CONNECTION



PHASOR DIAGRAM

Remark: Dimensions here are in inches. Only for approval/preliminary design.


No.	Name	Model	Qty.	Material	Remark
23	fans				provision only
22	SS hinges&pins				
21	padlock	penta-head bolt	1		
20	current limiting fuse		3		
19	insulation oil	Mineral oil			
18	gas sample valve		1		Schrader Valve
17	drip shield		1		
16	parking stand		6		
15	nameplate		1		
14	grounding lug		1		
13	drain valve w/ sampler		1		
12	grounding lug	Ø25*20, M10	4		with copper bar
11	reinforcing rib	8mm steel	1		
10	LV bushing		4		6-hole spade
9	HV bushing	200A bushing	6	load break	with (3) arrester
8	off-circuit tap changer		1		
7	load breaker switch		1		4-position
6	temperature indicator		1		
5	oil indicator		1		
4	Bayonet fuse		3		w/ flapper valve
3	oil fill valve		1		
2	pressure relief valve		1		automatic action
1	pressure indicator		1		

LARSON MAGNETICS

9419 E US HWY 175,
KEMP, TX 75143

TITLE
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

DRAWN BY	DATE	REV
	09/2026	A
CHECKED BY	SHEET #	DRAWING #
	1 OF 2	101



THREE PHASE PAD MOUNTED TRANSFORMER
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

High Voltage		
Tap Position	Voltage (V)	Current (A)
1	21013	34.3
2	20500	35.2
3	20000	36.1
4	19500	37.0
5	19013	38.0
Low Voltage		
Voltage (V)		Current (A)
400		1804.3

Rated Capacity	1250	KVA
HV	20000	V
LV	400Y/230	V
Impedance	5.0-7.5	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	Dyn1	
Rated Frequency	60	Hz
Cooling Type	ONAN	

Product Code	343983		
Serial Number			
HV BIL	95	LV BIL	30
Winding Con.	HV:Cu	LV:Cu	
Temp. Rise	65		°C
Oil Capacity	245		GAL
Total Weight	3715		LBS
Body Weight	8327		LBS
Step-Up Operation:	NO		

Tank must be solidly grounded - NON-PCB Oil

Mineral Oil Insulating Fluid

Wire Connection

Phasor Diagram

Maximum operating pressures of liquid preservation system_____kPa (lbf/in2) positive and _____ kPa (lbf/in2) negative.
Tank designed for_____ kPa (lbf/in2) vacuum filling.(insert any portion of the transormer that cannot withstand the stated vacuum level (i.e., conservator, LTC boards, radiator.)
Liquid level below top surface of the highest point of the highest manhole flange at 25 °C_____ mm(in). Liquid level changes _____ mm(in)per 10°C change in liquid temperature.

ANSI C57.12.34-DOE 2016 Compliant-Manufactured 2026.09

LARSON MAGNETICS

Larson Magnetecs LLC

Kemp, TX USA

LARSON MAGNETICS


9419 E US HWY 175,
KEMP, TX 75143


TITLE		
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1		
DRAWN BY	DATE	REV
	09/2026	A
CHECKED BY	SHEET #	DRAWING #
	2 OF 2	102

REV	DESCRIPTION	DATE
A	PRODUCT DESCRIPTION	09/2026


MT-PML-R7-3P-DVP-1.25MVA-YK-LT
-DF-A6-BMP-CS-2B4-M1


LARSON ELECTRONICS®






Rated Capacity	Loss(w)		Dimensions(in)			Weight	
	No-load Loss (W)	On-Load Loss	W	D	H	Oil Capacity (gal)	Total Weight (lbs)
1.25 MVA	1300	8500	73	71	73	245	8327





WIRING CONNECTION



PHASOR DIAGRAM

Remark: Dimensions here are in inches. Only for approval/preliminary design.


No.	Name	Model	Qty.	Material	Remark
23	fans				provision only
22	SS hinges&pins				
21	padlock	penta-head bolt	1		
20	current limiting fuse		3		
19	insulation oil	Mineral oil			
18	gas sample valve		1		Schrader Valve
17	drip shield		1		
16	parking stand		6		
15	nameplate		1		
14	grounding lug		1		
13	drain valve w/ sampler		1		
12	grounding lug	Ø25*20, M10	4		with copper bar
11	reinforcing rib	8mm steel	1		
10	LV bushing		4		6-hole spade
9	HV bushing	200A bushing	6	load break	with (3) arrester
8	off-circuit tap changer		1		
7	load breaker switch		1		4-position
6	temperature indicator		1		
5	oil indicator		1		
4	Bayonet fuse		3		w/ flapper valve
3	oil fill valve		1		
2	pressure relief valve		1		automatic action
1	pressure indicator		1		

LARSON MAGNETICS

9419 E US HWY 175,
KEMP, TX 75143

TITLE
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

DRAWN BY	DATE	REV
	09/2026	A
CHECKED BY	SHEET #	DRAWING #
	1 OF 2	101



THREE PHASE PAD MOUNTED TRANSFORMER
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1

High Voltage		
Tap Position	Voltage (V)	Current (A)
1	21013	34.3
2	20500	35.2
3	20000	36.1
4	19500	37.0
5	19013	38.0
Low Voltage		
Voltage (V)		Current (A)
400		1804.3

Rated Capacity	1250	KVA
HV	20000	V
LV	400Y/230	V
Impedance	5.0-7.5	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	Dyn1	
Rated Frequency	60	Hz
Cooling Type	ONAN	

Product Code	343983		
Serial Number			
HV BIL	95	LV BIL	30
Winding Con.	HV:Cu	LV:Cu	
Temp. Rise	65		°C
Oil Capacity	245		GAL
Total Weight	3715		LBS
Body Weight	8327		LBS
Step-Up Operation:	NO		

Tank must be solidly grounded - NON-PCB Oil

Mineral Oil Insulating Fluid

Wire Connection

Phasor Diagram

Maximum operating pressures of liquid preservation system_____kPa (lbf/in2) positive and _____ kPa (lbf/in2) negative.
Tank designed for_____ kPa (lbf/in2) vacuum filling.(insert any portion of the transormer that cannot withstand the stated vacuum level (i.e., conservator, LTC boards, radiator.)
Liquid level below top surface of the highest point of the highest manhole flange at 25 °C_____ mm(in). Liquid level changes _____ mm(in)per 10°C change in liquid temperature.

ANSI C57.12.34-DOE 2016 Compliant-Manufactured 2026.09

LARSON MAGNETICS

Larson Magnetecs LLC

Kemp, TX USA

LARSON MAGNETICS

9419 E US HWY 175,
KEMP, TX 75143

TITLE		
MT-PML-R7-3P-DVP-1.25MVA-YK-LT-DF-A6-BMP-CS-2B4-M1		
DRAWN BY	DATE	REV
	09/2026	A
CHECKED BY	SHEET #	DRAWING #
	2 OF 2	102

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs