

PM-Q500FWG

500 Watt Quartz Light

Product ID: 48757



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

PM-Q500FWG 500 Watt Quartz Flood Light

Lamp Type: Quartz Halogen

Lighting Configuration: Flood Pattern

Watts: 500

Voltage: 120V AC 50/60 HZ, 220V AC, 50/60 HZ, 240V AC 50/60 HZ, 12V DC, or 24V DC

Mounting: Adjustable Swivel Bracket with Pendant Mount

Wiring: 1/2" NPT

Features

Adjustable Lamp Head

3,300 Square Feet of Illumination

Dust-Tight

IP66

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The PM-Q500FWG quartz halogen flood light from Larson Electronics is capable of illuminating an area 3,300 square feet in size. This compact quartz floodlight is dust tight and comes with an adjustable mount that operators to easily install and adjust this fixture for optimal coverage.

The versatile PM-Q500FWG quartz halogen floodlight from Larson Electronics comes with an adjustable trunnion mount and a wide NEMA 6X6 beam spread that makes it ideal for industrial applications, maintenance, cleaning and servicing duties, large open space areas and any area where a wide flood beam is required. This unit contains a single 500 watt quartz halogen lamp and is capable of illuminating 3,300 square feet of work space.

The adjustable pendant/conduit mounting bracket on this unit allows for precise aiming of the light output of this fixture. The housing is comprised of a cast aluminum finned housing, high temperature silicone gasket, thermal shock-resistant tempered glass lens, and a double spring loaded socket for increased vibration resistance. The lamp head is adjustable and can be moved horizontally and vertically and locked into place. A separate wire connection box ensures ease of wiring during installation. The hinged door frame assembly aids in lamp replacement and maintenance repairs. This versatile work light can be used as an overhead light, exterior light, work area flood light, pulp and paper production, emergency evacuation, and just about anywhere economical yet powerful illumination is needed.









Frequently Asked Questions (FAQ)