Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-48-4L-LED-G2

Explosion Proof LED Lights for Paint Spray Booth - 2nd Gen - Class 1 & 2 - 4 Foot 4 Lamp - T6 Temp

Product ID: 64387



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-48-4L-LED-G2 Explosion Proof
NRTL Listed for United States & Canada
Dimensions: W-22.50" x L-52" x H-8.5 "
Weight: 95 Lbs

Total Watts: 112 watts

Voltage: Universal 120-277VAC 50/60 Hz or 12-24V AC/DC
LED Lamp Life Expectancy: 50,000+ Hours
Luminous Efficiency: 120 Lumens per Watt
Ambient Operating Temp Range: -30°C to +85°C
Operating Temp Rating: T6 Rated
Minimum Operating Temp: -30°C
Maximum Case Temp: +90°C
Beam Angle: 150°
Color Temp: 5600K or 4500K
Unistrut Mounting: Surface Mount Standard - Pendant Optional
Wiring Hub: 1/2 inch threaded

Ratings
Class 1 Division 1, Groups C and D
Class 1 Division 2, Groups A,B,C,D
Class II, Division 1&2, Groups E,F,G
NRTL Certified to UL 595 Outdoor Marine Type (Saltwater)
NRTL Certified to UL 1598 Marine Type
NRTL Certified to UL Certified Canadian Standards
NRTL Certified to UL listed for Paint Spray Booths
NRTL Certified to UL 844 924
California Title 24 Compliant

Special Orders- Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPL-48-4L-LED-G2 Explosion Proof LED Light Fixture NRTL Listed for United States and Canada Class 1 Division 1 & 2 and Class 2 Division 1 & 2 for areas where flammable petrochemical vapors and/or pulverized dust exist or have the potential to exist. This explosion proof LED light has a T-6 temperature rating and carries a paint spray booth light certification as well, making it ideal for applications such as paint booths, oil rigs, offshore applications, petrochemical,

manufacturing, chemical storage, water treatment centers, and food processing plants.

******PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE******


This 4 foot long 4 lamp LED fixture is ideal for operators seeking a top quality explosion proof light that will reduce operating costs, improve lighting quality and reduce downtime incurred from frequent servicing intervals. The EPL-48-4L-LED-G2 is equipped with Larson Electronics' specially designed LED T-series bulbs which produce 13,440 lumens, resulting in 30% more foot candles of illumination at 8 feet as compared to standard T8 lamps when measured with an Extech light meter. Our LED-T series bulbs are visibly brighter than standard T8`s and have consistently surprised many of our customers with their unexpectedly high light output levels. We have replaced four 8 foot dual lamp T8 fixtures in our own facility with our LED T series lamps and produced more illumination in the work area with only one 4 lamp 4 foot long LED fixture.

We now offer our second generation LED tube lamps with this fixture which have increased this hazardous location light's performance. This four lamp explosion proof LED linear fixture is lighter in weight, has a slimmer profile, and produces more light than traditional explosion proof fluorescent fixtures. The four foot long LED tube design bulbs included with this unit are rated at 50,000 hours of service life, which is over twice as long as standard T8 bulbs.

This fixture carries a T6 temperature rating and is Class 1 Division 1, Groups C and D, Class 1 Division 2, Group A, B, C and D, and Class II, Division 1 and 2, Groups E, F and G. Click here to read the NEC description for explosion proof and hazardous locations.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

We have eliminated the ballast box normally associated with fluorescent fixtures which reduces overall weight and creates a slimmer unit profile. There is no ballast in this unit and the included LEDT8-28W-V1 LED lamps have a 50,000+ hour service life, both of which result in extreme efficiency and greatly reduced maintenance costs. The solid state design of the LED lamps give this fixture superior resistance to damage from vibration, extremes in temperature and a lamp service life over twice that of standard fluorescent bulbs.

Unlike the glass tube design of traditional fluorescent lamps, these LED T-Style lamps have no filaments or fragile housings to break during operation. Instead of using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. The LED assembly is mounted to the "tube" constructed from extruded aluminum, with a polycarbonate lens protecting the LEDs. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than fluorescent lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional fluorescent lighting.

The 28 watt LED lamps produce 30% more illumination than standard T8 bulbs while offering lower amp draw and increased reliability. Each lamp produces 3360 lumens at 120 lumens per watt, for a combined 13,440 total lumen light output.

An EPL-48-4L-T8 explosion proof fluorescent light, with a combined total of 128 watts, draws 1.07 amps at 120 volts AC. This LED version of the same light, with a total of 112 watts, draws only 0.93 amps at 120 volts AC. The EPL-48-4L-LED-G2 is universal voltage, not multi-tap, and operates on any voltage from 120V to 277V AC 50/60hz without any modifications. We also make a 12/24V AC/DC version for low voltage applications for AC or DC power.

Energy Consumption Comparison

	T5HO	T8	LED
Wattage	216 watts	128 watts	112 watts
Amp Draw @ 120V AC	1.80 amps	1.07 amps	0.93 amps
Amp Draw @ 220V AC	0.98 amps	0.59 amps	0.51 amps
Amp Draw @ 240V AC	0.90 amps	0.54 amps	0.47 amps
Amp Draw @ 277V AC	0.78 amps	0.47 amps	0.40 amps
Amp Draw @ 12V DC	18 amps	10.67 amps	9.33 amps
Amp Draw @ 24V DC	9 amps	5.34 amps	4.67 amps
Lamp Life Expectancy	20,000 hours	24,000 hours	50,000 hours
Color Temperature	5000K / 4100K	4100K	5600K
Operation cost per year (12hs/day @ 12c/kWh)	$113.53	$67.28	$58.86

Our EPL-48-4L-LED-G2 LED light fixture is NRTL Listed for United States and Canada for use in paint spray booths. Please note, according to the NEC, using threaded rigid pipe does not require additional seal offs with this fixture. An EYM and seal off is necessary for flex conduit or other non-rigid pipe implementations.
Mounting Options: Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.
Mounting: Standard end mounting via Unistrut. The Unistrut is attached to our standard L-bracket mounts. These L-bracket mounts can be adjusted to create angle mounts. As illustrated in the photos above, the series of mounting holes at the top of the bracket enable this explosion proof LED light to be attached to any wall, ceiling or floor surface. A simple through bolt can be used to secure the light to the surface. A single junction box at one end of the light is provided for the electrical connection.
Suspension Mounting: Pendant mount fixtures hang from the ceiling and are suspended by rigid pipe. Each fixture features a 1/2" NPT junction box on one end, and a 1/2" NPT bracket on the other end of the fixture. Operators bring rigid pipe down to the threaded mounting hubs. Wiring is fed down through the rigid pipe to the junction box and tied in to the fixture's lead wires, completing the electrical connection. The threaded mounting bracket provides support for the opposite end of the fixture.
Suggested Applications: Paint spray booths, aircraft maintenance, oil drilling rigs, refineries, solvent and cleaning areas, gas processing plants, chemical manufacturing, waste treatment plants, gas processing plants.

Made in USA Quality


1. Each unit dialectrically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy
4. No ballast box. No ballast to replace. .
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for re-lamping the fixture, while some competitive models require the "tap

Superior LED Benefits


1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.


and knock off" method to loosen the end cap.
7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.
8. Spring loaded sockets on both ends hold lamps firmly for maximum shock and vibration protection.
9. Lighter weight, slimmer, brighter alternative to fluorescent configurations

8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.


25.241
15.375


9.820
52.262


0.625
44.884
52.262











Frequently Asked Questions (FAQ)