

EPL-TL-3X10W-C

Explosion Proof Traffic Light - Class 1 & Class 2 Signal Stack Light - Red, Yellow, Green Stop & Go

Product ID: 69071



Image: EPL-TL-3X10W-C

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-TL-3X10W-C Explosion Proof LED Stack Light

Lamp Type: LED

Dimensions:

Wattage: 10 Watts per Lamp - 30 Watts Max

Lamp Color: Red, Amber, Green (other color configurations available upon request)

Voltage: 120-277 Volts AC, 11 or 25 Volts DC or AC

Mounting: Predrilled Aluminum Flat Surface Mounting Bracket

Temp Rating: T3C

Lighting Configuration: Steady Burn, Strobe, Configuration 1 (Lamp 1: Strobe, Lamp 2: Strobe, Lamp 3: Steady Burn)

Lamp Life: 50,000+ Hours

Wiring: 10' SOOW Cable w/ Flying Leads

Ratings/Approvals

Listed for United States & Canada

Class 1, Division 1 & 2, Groups C and D

Class 2, Division 1 & 2, Groups E, F and G

Class 3, Division 1 & 2

IP67 (water proof)

T3C Temperature Rating

New York City Department of Buildings approved

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Made in the USA

The EPL-TL-3X10W-C Class 1, Division 1 and Class 2 Division 1 LED Signal Stack Light from Larson Electronics is approved for use in wet locations and marine environments. This

explosion proof LED stack light is designed for routing traffic and signaling, and visual indications in industrial refueling stations and process status indication in manufacturing facilities.

The EPL-TL-3X10W-C explosion proof LED traffic light from Larson Electronics is an ideal indicator lighting solution for industrial refueling stations and manufacturing facilities. The light housings are constructed with a polyester powder coated copper free aluminum casting that can withstand 1490 pounds PSI hydrostatic pressure. The mounting plate is constructed of non-sparking aluminum and can be custom built to customer specifications. This explosion proof red and green indicator light has a 50,000 hour operational life and is available in 120-277 VAC and 11 or 24 VDC or VAC configurations for standard or low voltage operation.



[Click Image to Enlarge](#)



[Click Image to Enlarge](#)



[Click Image to Enlarge](#)

This explosion proof LED stack light carries a T3C temperature rating and has a -40°C to +85°C ambient operating temperature range. The EPL-TL-3X10W-C is Class 1, Class 2, Class 3, Division 1 & 2 approved. Line-in supply power is provided by 10' of 16 AWG SOOW cable with flying leads. Individual leads per lamp allow independent operation, making this unit ideal for fuel depots and manufacturing facilities where status indicators are necessary. The individual leads can be connected to user provided terminal blocks or existing indicator systems.

Unlike traditional indicator lamps that use a colored globe with low color temperature incandescent lamps, this explosion proof LED stack light incorporates a clear glass globe and colored LED lamps. By utilizing colored LEDs instead of tinted lenses or globes, the total visibility and light output is increased when compared to traditional colored lamps. This is particularly important for strobe configurations, increasing the peak candela of the signal during indications. The standard lamp configuration is red, amber, and green LED bulbs in a steady burn or strobing configuration. We offer a large assortment of lamp color options including red, green, blue, amber, purple, and white LED lamps. Please contact us for special lamp configurations. These stack lights can also be configured with audible horns.

Commonly used color codes for indicators:

- Red: Stop / Failure conditions, such as an emergency stop or machine fault
- Yellow: Caution / Warnings, such as over-temperature or over-pressure conditions
- Green: Go / Normal machine or process operation
- Blue: External help request / Operator/Supervisor required / Maintenance personnel assistance required
- White: User-defined conditions specific to application and environment

Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than traditional lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional lighting.


This explosion proof fixture is configured for red, amber, and green output (one lamp each color) offers exceptional lumen output, a 50,000+ hour life span, and the lamps are protected by Pyrex globes and cast aluminum globe guards. The LED lamps in this traffic light are 10 watts each and offer cool operation and clean bright output that surpasses that of 100 watt incandescent indicator lamps. Mounting is provided by a heavy gauge aluminum back plate fabricated from copper free aluminum with four predrilled holes designed to be bolted to walls, ceilings, and flat surfaces for permanent and secure attachment.

Note on Lights: Please note, the color choices and light configuration of this unit can be customized to your requirements. We offer steady burn or strobing LED lamps, as well as high or low voltage configurations. Please contact us for special color configurations.

Voltages: 120-277VAC 50/60Hz, 11 or 25V AC/DC





Temp Code: Class 1 T3C Groups C,D : Class 2 - T3C Groups E,F,G

8	7	6	5	4	3	2	1
REV	DESCRIPTION						DATE
A	PRODUCTION RELEASE						4/19/2022
EPL-TL-3X10W-C-1227VAC-STB- RED.YLW.GRN 							
8	7	6	5	4	3	2	1



TAGS	QTY	CATALOG	DESCRIPTION
LT1-101.15	1	UNV00008059	10W A19 LED BULB GREEN STEADY BURN 1227
LT1-101.10	1	UNV00008068	10W A19 LED BULB YELLOW STEADY BURN 1227
LT1-101.05	1	UNV00008063	10W A19 LED BULB RED STEADY BURN 1227
CBL1-101.10	10'	UNV00002853	16/7 SOOW CABLE

 LARSON ELECTRONICS 9419 E US HWY 175, KEMP, TX 75143	TITLE EPL-TL-3X10W-C-1227VAC-STB- RED.YLW.GRN		
	DRAWN BY M.RAHMAN	DATE 4/19/2022	REV A
	CHECKED BY K.NGUYEN	SHEET # 1 OF 1	DRAWING # 101



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
LARSON ELECTRONICS LLC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
LARSON ELECTRONICS LLC IS
PROHIBITED.

DIMENSIONS ARE IN INCHES		DRAWN	NAME	TITLE:	
MATERIAL		CHECKED	CHRIS THAUER	EPL-TL-3X10W-C	
DO NOT SCALE DRAWING			JEREMY BLANKENSHIP	SIZE A	DWG. NO.
				SCALE: 1:10	REV
				SHEET 1 OF 1	

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Certification

Manufacturer: Larson Electronics LLC
Address: 9419 US-HWY 175
Kemp, Texas 75143

Declare the following equipment conforms to the standard(s) as listed:

Model: EPL-TL Series
Description: Explosion Proof Stack Lights w/o Horn

Evaluated Listings:

UL: E10514, E91793 – NEC / United States standards
UL: E10514 – CEC / Canada standards
CSA: LR11716 – CEC / Canada standards
ETL: UL 508A, UL 1203 – NEC / United States standards
ETL: CSA C22.2 No. 14, No. 25, No. 30 – CEC / Canada standards

The EPL-TL Series is certified to NEC and CEC standards for hazardous locations for:

- NEC: Class I, Divisions 1 & 2, Groups C & D; Class II, Divisions 1 & 2, Groups E, F, G
- NEC: Class I, Zones 1 & 2, Groups IIB, IIA
- CEC: Class I, Divisions 1 & 2, Groups C & D; Class II, Divisions 1 & 2, Groups E, F, G
- CEC: Class I, Zones 1 & 2, Groups IIB, IIA

The EPL-TL Series comprised of a Killark EMI series device enclosure(s). This device enclosure(s) may contain an incandescent, compact fluorescent, or LED lamp and custom mounting of the lamp assembly to prevent damage. One or multiple fixtures are mounted to a copper free aluminum mounting plate, junctioned together utilizing galvanized rigid conduit, and may utilize unique signal wires per lamp. Lamp(s) may be configured as steady burn or strobe light output and may be of different light output colors per device enclosure. This assembly is built to NEC and CEC standards for hazardous locations and quality checked per ISO 9001:2015 standards.

Signed for and on behalf of: Larson Electronics, LLC
Place of issue: Kemp, TX

Signature: *James Thomas*

Name: James Thomas
Position: Operations Manager

[<- Back](#)

Product Description

Title: INDUSTRIAL CONTROL PANELS
Company: LARSON ELECTRONICS LLC - Kemp, TX USA
Product Information: Industrial Control Panels For General Use.
Evaluated to the following: A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Industrial Control Panels (UL-508A) and are identified with the ETL Listed Mark.

[<- Back](#)

Contact Us

ETL listed products that are in doubt or for products that do not appear in the directory, please request a verification of certification.
Americas+1-888-347-5478
(or +1-847-660-7407)
Email
etldirectory@intertek.com

[Intertek Home](#)
[Product Directories](#)
[DLP on mobile devices](#)

Inspector Center

Get up-to-date information on everything from our Accreditations to our Certifications and Marks. [Learn more...](#)

News

Intertek Unveils New Design for Product Safety and Quality Certification Marks. [Learn more...](#)

© 2010 Intertek All Rights Reserved.
All other product or service names are the property of their respective owners.

[<- Back](#)

Product Description

Title: EXPLOSION-PROOF & DUST IGNITION-PROOF ELECTRICAL EQUIPMENT FOR USE IN HAZARDOUS (CLASSIFIED) LOCATIONS

Company: LARSON ELECTRONICS LLC - Kemp, TX USA

Product Information: Explosion-proof or dust-ignition-proof Industrial Control Panels for use in Hazardous (Classified) Locations, Model Nos. Custom Industrial Control Panels

Evaluated to the following: A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Explosion-Proof and Dust Ignition-Proof Electrical Equipment for Use in Hazardous (Classified) Locations (UL-1203) and are identified with the ETL Listed Mark.

[<- Back](#)

Contact Us

ETL listed products that are in doubt or for products that do not appear in the directory, please request a verification of certification.
Americas+1-888-347-5478
(or +1-847-660-7407)
Email
etldirectory@intertek.com

[Intertek Home](#)
[Product Directories](#)
[DLP on mobile devices](#)

Inspector Center

Get up-to-date information on everything from our Accreditations to our Certifications and Marks. [Learn more...](#)

News

Intertek Unveils New Design for Product Safety and Quality Certification Marks. [Learn more...](#)

© 2010 Intertek All Rights Reserved.
All other product or service names are the property of their respective owners.

[<- Back](#)

Product Description

Title: INDUSTRIAL CONTROL EQUIPMENT
Company: LARSON ELECTRONICS LLC - Kemp, TX USA
Product Information: Industrial Control Panels For General Use.
Industrial Control Panels Relating to Hazardous (Classified) Locations, Custom Industrial Control Panels.

Power Distribution System, Model Nos. MGL, MPD, MGS series;
Followed by AAK-PBB.FFF-SCC.GGG-EEXCCC.DDD; Where AA = 2,3,5,7,9,15,20,25,30,45,50,75; BB = 1P, 3P; FFF = 480,240,208,120; CC = 1P,3P; GGG = 480,240,208,120; EE = # of outlets; CCC = voltage; DDD = outlet amperage.

Evaluated to the following: A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Industrial Control Equipment (CAN/CSA-C22.2 No. 14) and are identified with the cETL Listed Mark.

[<- Back](#)

Contact Us

ETL listed products that are in doubt or for products that do not appear in the directory, please request a verification of certification.
Americas+1-888-347-5478
(or +1-847-660-7407)
Email
etldirectory@intertek.com

[Intertek Home](#)
[Product Directories](#)
[DLP on mobile devices](#)

Inspector Center

Get up-to-date information on everything from our Accreditations to our Certifications and Marks. [Learn more...](#)

News

Intertek Unveils New Design for Product Safety and Quality Certification Marks. [Learn more...](#)

© 2010 Intertek All Rights Reserved.
All other product or service names are the property of their respective owners.

[<- Back](#)

Product Description

Title: ENCLOSURES
Company: LARSON ELECTRONICS LLC - Kemp, TX USA
Product Information: Explosion-proof or dust-ignition-proof Industrial Control Panels for use in Hazardous (Classified) Locations, Model Nos. Custom Industrial Control Panels

Luminaires, Model Nos. EPL-48-2L-LED-SFC, EPL-24-2L-LED-SFC. for use in Hazardous Locations: Class I, Div. 1, Groups C and D T5 or T6 -20°C < Tamb < 40°C Class II, Div. 1., Groups E, F, and G; Class III Div.1 T3B -20°C < Tamb < 40°C

Evaluated to the following: A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Enclosures for use in Class II, Groups E, F, G Hazardous Locations (CAN/CSA-C22.2 No. 25) and are identified with the cETL Listed Mark.

[<- Back](#)

Contact Us

ETL listed products that are in doubt or for products that do not appear in the directory, please request a verification of certification.
Americas+1-888-347-5478
(or +1-847-660-7407)
Email
etldirectory@intertek.com

[Intertek Home](#)
[Product Directories](#)
[DLP on mobile devices](#)

Inspector Center

Get up-to-date information on everything from our Accreditations to our Certifications and Marks. [Learn more...](#)

News

Intertek Unveils New Design for Product Safety and Quality Certification Marks. [Learn more...](#)

© 2010 Intertek All Rights Reserved.
All other product or service names are the property of their respective owners.

[<- Back](#)

Product Description

Title: EXPLOSION-PROOF ENCLOSURES FOR USE IN CLASS I HAZARDOUS LOCATIONS

Company: LARSON ELECTRONICS LLC - Kemp, TX USA

Product Information: Explosion-proof or dust-ignition-proof Industrial Control Panels for use in Hazardous (Classified) Locations, Model Nos. Custom Industrial Control Panels

Evaluated to the following: A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Explosion-Proof Enclosures for Use in Class I Hazardous Locations (CAN/CSA-C22.2 No. 30) and are identified with the cETL Listed Mark.

[<- Back](#)

Contact Us

ETL listed products that are in doubt or for products that do not appear in the directory, please request a verification of certification.
Americas+1-888-347-5478
(or +1-847-660-7407)
Email
etldirectory@intertek.com

[Intertek Home](#)
[Product Directories](#)
[DLP on mobile devices](#)

Inspector Center

Get up-to-date information on everything from our Accreditations to our Certifications and Marks. [Learn more...](#)

News

Intertek Unveils New Design for Product Safety and Quality Certification Marks. [Learn more...](#)

© 2010 Intertek All Rights Reserved.
All other product or service names are the property of their respective owners.



Material Safety Data Sheet

To Whom It May Concern,

Larson Electronics LLC EHL, EPL, EPLC2, HAL, HALP, HALD, HAL-LI, HALS, and HALSS industrial line of LED lights without emergency backup for hazardous locations are considered “ARTICLES” under 29 CFR 1910-1200, the OSHA Hazard Communication Standard, and do not require a Material Safety Data Sheet (MSDS).

Articles are specifically exempt from the regulations of this standard. OSHA defines an article as follows:

1910-1200(c) – Article means a manufactured item other than a fluid or particle:

- i. Which is formed to a specific shape or design during manufacture;
- ii. Which has end use function(s) dependent in whole or in part upon its shape or design during end use; and
- iii. Which under normal conditions does not release more than very small quantities.

The “hazardous location” and “explosion proof” are terminology for the environment where these products will be installed. This is not to be confused with “hazardous materials;” this product does not contain any hazardous materials.

Regards,

Ray Smith
Larson Electronics, LLC.



IHSN.E10514 - Luminaire Fittings for Use in Zone Classified Hazardous Locations

Luminaire Fittings for Use in Zone Classified Hazardous Locations

See General Information for Luminaire Fittings for Use in Zone Classified Hazardous Locations

KILLARK, DIV OF HUBBELL INC (DELAWARE)

E10514

2112 FENTON LOGISTICS PARK BLVD

FENTON, MO 63026 USA

Class I, Zone 1, AEx d IIB.

Series EZM, EZH or EZS followed by 10, 15, 17, 25, 40, 50 or 70, followed by 0, 1, 2, 3, 4, 5, 6, 7 or 8, followed by A2, A3, B2, B3, D4, D5, X2 or X3, may be followed by G, PS, BP or R.

Series EMI or EBF followed by 13, 15, 20, 26 or 30, followed by A2, 3, B2, B3, D4, D5, X2 or X3, may be followed by G.

Series EMS, EMM or EMH followed by 35, 05, 07, 75, 10, 15, 13, 26, followed by, followed by 0, 1, 2, 3, 4, 5, 6, 7 or 8, followed by A2, A3, B2, B3, D4, D5, X2 or X3, may be followed by G.

Trademark and/or Tradename: "E10514", "Killark/Chalmit"

Last Updated on 2015-10-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

[HOME \(HTTPS://WWW.CSAGROUP.ORG/\)](https://www.csagroup.org/) / [TESTING AND CERTIFICATION \(HTTPS://WWW.CSAGROUP.ORG/TESTING-CERTIFICATION/\)](https://www.csagroup.org/testing-certification/) / [CSA GROUP PRODUCT LISTING \(HTTPS://WWW.CSAGROUP.ORG/TESTING-CERTIFICATION/PRODUCT-LISTING/\)](https://www.csagroup.org/testing-certification/product-listing/) /
CERTIFICATION RECORD

Certification Record

Contact an Expert
(<https://www.csagroup.org/contact/>)

CUSTOMER	CLASS	FILE NUMBER
Killark, Div of Hubbell Inc. (Delaware) 2112 Fenton Logistics Park Blvd, Fenton Missouri United States 63026	3428-03 (../class/?class=3428-03) FIXTURES AND FITTINGS-For Hazardous Locations	011713_C_000

Class I, Groups C and D; Class II, Groups E, F and G; Class III;

(Temperature Coded), CSA Encl. 3 and 4 (component packaged):

- Series "HZ" integral ballast with or without aux. quartz lamp 100 or 150W, (for Div 1 only) 480V max, 60Hz, pendant ceiling, bracket, bulk-head or stanchion mount, max 400W high pressure sodium; 250 and 400W mercury vapour or metal halide. Suffix letters and digits following Series "HZ" denote lamp type, wattage, voltage, guard option, mounting conduit , globe and aux. lamp options.
- Temperature coded as follows: HPS without quartz lamp (T3C), with quartz lamp (T2D). 200 and 400W, MH and MV, without quartz lamp (T3A), with quartz lamp (T2D).

Class I, Groups C and D; Class II, Groups E, F and G; Class III; (Temperature Coded); CSA Encl 3, 4, 4X:

Class I, Division 2, Groups B, C and D; Class II, Division 2, Groups E, F and G; Class III; CSA Encl 3, 4, 4X:

- Series EZ luminaires, mercury vapour (MV), metal halide (MH) or high pressure sodium (HPS) and EZL - LED, 190W max; 50/60 Hz, 480 VAC max or 250VDC max; lamp wattage 400 W max; 60 Hz, 600 V max.

Note: Suffixes letters/numerals denote Lamp Type, Lamp Ratings, Voltage, Mounting and Options.

Temperature coded as follows:

				Suitable For Simultaneous Use In Class	
	Lamp		Rated Ambient	Class I Div. 1	Groups C, D and Class
Cat No	W	Type+	C	Groups	II, Groups
*EZS50	50	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS50	50	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)
EZS50	50	HPS	65	C,D 120(T4A)	E,F,G 165 (T3B)
*EZS07	70	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS07	70	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)
EZS07	70	HPS	65	C,D 120(T4A)	E,F,G 165 (T3B)
*EZS10	100	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS10	100	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)
EZS10	100	HPS	65	C,D 120(T4A)	E,F,G 165 (T3B)
EZS15	150	HPS	40	C,D 120(T4A)	E,F,G 160 (T3C)
EZS15	150	HPS	55	C,D 120(T4A)	E,F,G 160 (T3C)

Contact an Expert
(https://www.csagroup.org/contact/)

Contact an
Expert

We're always here to help. Let's talk.

We're here to answer your questions and help you get started right away. Call or send us a message anytime.

[Contact Us \(https://www.csagroup.org/contact\)](https://www.csagroup.org/contact)

Contact an Expert
(https://www.csagroup.org/contact/)



(https://www.csagroup.org)

[FAQs \(/faq/\)](#)

[CSA OnDemand™](#)

(http://store.csagroup.org/ondemand/s/?language=en_US)

[Informs & Notices \(/informs-notices/\)](#)

[Submit an Incident Report \(/submit-a-report\)](#)

[Agreement on Acceptance of Components \(/agreement-acceptance-components/\)](#)

[CSA Communities \(http://community.csagroup.org/login.jspa?referer=%252Findex.jspa\)](#)

[Product Alerts & Recalls](#)

(/product-alerts-recalls/)

[Report Suspect Counterfeit Marks \(/testing-certification/marks-labels/brand-protection/reporting-suspect-counterfeit-marks\)](#)

[Resources & Insights \(/resources-insights/\)](#)

[Standards Research \(/standards/standards-research/\)](#)

[CSA Group Product Listing \(/testing-certification/product-listing/\)](#)

[Sign up for our Newsletter](#)

(https://www.csagroup.org/newsletter/)

[\(http://www.facebook.com/CSAGroup\)](#)

[\(http://www.linkedin.com/company-csa-group\)](#)

[/csa-1135116272144416000](#)

[\(http://www.youtube.com/channel/UCSA_Group/standards/\)](#)

[Legal \(https://www.csagroup.org/legal/\)](#)

[Privacy Policy \(https://www.csagroup.org/legal/privacy-policy/\)](#)

© 2020 [CSA Group \(https://www.csagroup.org\)](#)

[Evidence of Insurance \(https://www.csagroup.org/legal/evidence-of-insurance/\)](#)

[HSSE Policy \(https://www.csagroup.org/hsse-policy/\)](#)

[Accreditation \(https://www.csagroup.org/accreditation/\)](#)

[Annual Report \(https://www.csagroup.org/annual-report/\)](#)



Certification

Manufacturer: Larson Electronics LLC
Address: 9419 US-HWY 175
Kemp, Texas 75143

Declare the following equipment conforms to the standard(s) as listed:

Model: EPL-TL Series
Description: Explosion Proof Stack Lights w/o Horn

Evaluated Listings:

CE: EN 60598-2-5:2015
CE: EN 62560:2012/AC:2015

The EPL-TL Series complies with the essential protection requirements of the European Parliament of the Council Directive 2014/34/EU on the approximation of the laws of the Member States relating to electrical apparatuses operating within the range of 50-1000 volts AC or 75-1500 volts DC. This certification applies to all specimens manufactured in accordance to the manufactures drawings.

Signed for and on behalf of: Larson Electronics, LLC
Place of issue: Kemp, TX

Signature: *James Thomas*

Name: James Thomas
Position: Operations Manager



Certification

Manufacturer: Larson Electronics LLC
Address: 9419 US-HWY 175
Kemp, Texas 75143

Declare the following equipment conforms to the standard(s) as listed:

Model: EPL-TL Series
Description: Explosion Proof Stack Lights w/o Horn

Evaluated Listings:

CE: DIRECTIVE 2015/863/EU - ROHS DIRECTIVE

This is to certify that products offered by Larson Electronics LLC comply with the Reduction of Hazardous Substances (RoHS) directives. Directive 2002/95/EC became effective on 1 July 2006. It restricts the use of six substances in the manufacture of electrical and electronic equipment. This directive was revised in June 2011 and is now referred to as directive 2011/65/EU. Directive 2015/863/EU amending Annex II to Directive 2011/65/EU announced plans to add four substances from 22 July 2019.

We hereby certify that the equipment specified above conforms to the Directive(s) by containing less of the restricted substances than the stated limits.

Signed for and on behalf of: Larson Electronics, LLC
Place of issue: Kemp, TX

Signature: *James Thomas*

Name: James Thomas
Position: Operations Manager



Certification

Manufacturer: Larson Electronics LLC
Address: 9419 US-HWY 175
Kemp, Texas 75143

Declare the following equipment conforms to the standard(s) as listed:

Model: EPL-TL Series
Description: Explosion Proof Stack Lights w/o Horn

Evaluated Listings:

CE: Regulation (EC) No 1907/2006 - REACH REGULATION

This letter establishes the opinion of Larson Electronics LLC regarding the status, under the current European Union ("EU") Regulations on Registration, Evaluation, Authorization, and Restriction of Chemical Substances ("REACH").

REACH does not apply to manufactured products which are referred to as "completed articles". Substances (chemicals) are subject to REACH registration, NOT products.

In addition, Articles are exempt from the REACH requirements if (a) the Article does not contain a substance of very high concern or candidate substance in an amount exceeding 0.1% weight by weight, and (b) if substances present in the Article in excess of 1 ton per year per importer are not expected nor intended to be released.

Based on communication with our raw material suppliers, we conclude that to the best of our knowledge our products requiring REACH compliance do not contain any of the currently listed SVHC in concentrations of 0.1% or above.

Accordingly, we foresee no registration or pre-registration requirement for the products we supply.

Signed for and on behalf of: Larson Electronics, LLC
Place of issue: Kemp, TX

Signature: *James Thomas*

Name: James Thomas
Position: Operations Manager



Frequently Asked Questions (FAQ)

There are no Faqs