Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-24-2L-LED-BMSW-G2

Hazardous Location Lighting LED Pivoting Light - 2 foot 2 lamp - 2nd Gen LED Lamps

Product ID: 69991



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-24-2L-LED-BMSW-G2 Hazardous Area

Dimensions: W-7" L-25 1/2" H-6 1/8"

Weight: 14 Lbs

Total Watts: 28 watts

Voltage: Multi- 120V-60hz 220V-50hz 240V-60hz 277V-60hz

Low Voltage (Optional): 12-24V DC

LED Lamp Life Expectancy: 50,000 Hours

Efficiency: 125 Lumens per Watt

Operating Temp Range: T4A rated -30 C to 85 C

Beam Angle: 150 degrees

Color Temp: 5300K- Color Rendering Index-75

Mounting: Back Mount Swivel Bracket

Wiring Hub:1/2" or 3/4" threaded

Minimum Operating Temp: -30 C

Maximum Case Temp: 90 C

U.L. Ratings

NRTL Certified to UL 595 Outdoor Marine Type (Saltwater)

NRTL Certified to UL 1598A Marine Type

California Title 24 Compliant

NRTL Listed for United States & Canada

Class 1 Division 2, Groups A, B, C and D

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics HAL-24-2L-LED-BMSW-G2 Hazardous Area LED Light Fixture is NRTL Listed for United States & Canada, Class 1 Division 2 Groups A, B, C and D - NRTL Certified to UL 1598A, has a T4A temperature rating and ideal for hazardous locations where flammable chemical/petrochemical vapors may be occasionally encountered.

The HAL-24-2L-LED-BMSW-G2 fixture is a 2 foot long, 2 lamp, Class 1 Division 2

Groups A, B, C and D hazardous area LED light that takes the reliability and efficiency of a fluorescent fixture and adds even longer lamp life and efficiency with high output LEDs. This fixture is T4A temperature rated and comes standard with our high power 14 watt LED lamps. The lamps are protected by a powder coated aluminum frame and shatter and heat resistant clear acrylic lens secured with four zinc coated steel draw latches.
The fixture is constructed of copper free aluminum alloy and powder coated. The lamp reflector is corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture can be configured to run on 120 to 277VAC as well as 12-24VDC and is NRTL Certified to UL 595 and UL 1598A Marine Type approved for use marine environments. The HAL-24-2L-LED-BMSW is weatherproof and provides operators in hazardous locations with a highly efficient, reliable and affordable lighting solution for open areas where flammable chemicals and vapors may occasionally be present.



Click Photos to Enlarge




Click Photos to Enlarge



Click Photos to Enlarge







We have eliminated the ballast normally associated with fluorescent fixtures which reduces overall weight, increases lamp life to an extreme 50,000 hours and helps this LED fixture maintain a T4A temperature rating. The solid state design of the included LED lamps give this fixture superior resistance to damage from vibrations and extremes in temperature as well as a lamp service life over twice that of standard T8 bulbs. The 14 watt LED lamps produce more illumination than standard T8 bulbs, but draw only 3/4 of the current. The current generation of Larson Electronics LED T-series style bulbs produce 30% more light than standard T8 bulbs. This fixture is multi-voltage capable (not multi-tap) and works on the following voltages: 120 Volt 60 HZ, 220 Volt 50 HZ, 240 Volt 60 HZ, 277 Volts 60 HZ. We also make a 12-24V DC version for low voltage applications (-LV suffix). Our HAL-24-2L-LED-G2 LED light fixture is NRTL Listed for United States & Canada.
Standard Surface Mount Brackets: Each L bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two bolts on either side of the bracket. The bolts act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be pivoted by loosening the that hold the bracket to the mounting peg. This fixture allows 45 degrees of pivot from the 90 degree point.
Suggested Applications: Aircraft maintenance, Oil drilling rigs, Refineries, Solvent and cleaning areas, Chemical manufacturing, Waste treatment plants, Gas processing plants.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed streamlined ribbed corrosion-resistant, copper free extruded aluminum body for better hear dissipation and extended ballast life.
4. Aluminum extruded lens frame for greater strength
5. Relamping done via 10 draw latches, which enable the operator to unlatch the lens and access the lamps.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. 1/2" or 3/4", threaded access hole for wiring conduit.
7. Units can be wired end to end in series.


Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

REV	DESCRIPTION	DATE
A	PRODUCTION RELEASE	12/12/2023

HAL-24-2L-LED-BMSW-G2
-1224-XX-XX

LARSON ELECTRONICS®





TAGS	QTY	CATALOG	DESCRIPTION
LT1-101.08 LT1-101.11	2	UNV00008101	14W 2F T8 LED TUBE 5600K
W2	2	UNV00009802	2 HOLE WAGO


LARSON ELECTRONICS


9419 E US HWY 175,
KEMP, TX 75143

TITLE: HAL-24-2L-LED-BMSW-G2--1224-XX-XX			
DRAWN BY: S.Desai	DATE: 12/12/2023	REV: A	
CHECKED BY: J.Maldonado	SHEET #: 1 OF 1	DRAWING #: 101	









Larson Electronics

TITLE:

HAL-24-2L-LED-BMSW

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LARSON ELECTRONICS LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF LARSON ELECTRONICS LLC IS PROHIBITED.

		NAME
DIMENSIONS ARE IN INCHES	DRAWN	CHRIS THAUER
MATERIAL	CHECKED	JEREMY BLANKENSHIP
DO NOT SCALE DRAWING		

SIZE	DWG. NO.	REV
A		

SCALE: 1:8 | SHEET 1 OF 1

5 4 3 2 1


Larson Electronics
1-800-369-6671
Sales@LarsonElectronics.com







Frequently Asked Questions (FAQ)