

EPL-WPLED-70W-DL-B

Explosion Proof 70 Watt LED Wall Pack Down Light - 6000 Lumens - C1D1 & C1D2

Product ID: 70013



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-WPLED-70W-DL-B Low Profile Light

Lamp Type: LED

Dimensions: 10.7" Length, 9.7" Width, 5.8" Depth

Total Watts: 70W

Lumens: 6,000

Voltage: Multi- 100-277 VAC, 50/60Hz

Lighting Configuration: 180° directional flood

Mounting: 3/4" NPT or 5/16"-18 x .75" NPT Thread

Weight: 20lbs

U.L. Listing: Explosion Proof

Temp Rating: T5 -40C to +45C

Color Temp: 6000K, >70-CRI.

Lamp Life: 100,000+ Hours

Beam Spread: 180° or 360°

Ratings

T5 Temperature Rating

Class 1 Division 1&2 Groups C, D

Class 2 Division 1&2 Groups E,F,G

UL 844

UL-1598/A

IP66

NEMA 4X

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

E-mail: sales@larsonelectronics.com

The Larson Electronics EPL-WPLED-70W-DL-B wall pack LED down light fixture provides operators with a powerful and energy efficient alternative to traditional hazardous location luminaries. LED technology and compact design makes this lamp an excellent replacement upgrade option for bulky and high maintenance cost older fixtures.

This Class 1 Division 1 & 2, Class 2 Division 1 & 2 explosion proof light fixture provides 6,000 lumens of high quality light while drawing only 70 watts. It is available in 360° and 180° beam spreads. The copper free aluminum alloy body is powder coated for added durability and an attractive aesthetic appearance. A

special heat dissipating design in conjunction with advanced LED driver technology helps this fixture achieve an excellent 100,000 hour rated lifespan with 70% lumen retention. Light weight and a low profile make this unit an attractive alternative to larger and heavier older fixtures and requires less hardware to install.

This light is multi-voltage capable and can be operated with 100-277 VAC, 50/60Hz without any need for a ballast or transformer. The aluminum body and LED lamp assembly gives this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat, which increases the efficiency and lifespan of the LED emitters.

This high output LED lamp produces 6,000 lumens with a color temperature of 6000K and a color rendering index of 70, which means this lamp renders colors and details much more accurately than high pressure sodium or mercury vapor down lights. The optics of this explosion proof LED wall pack provide 180° of directional illumination. For optimal performance, this LED light fixture is recommended to be mounted at a 45° angle. The EPL-WPLED-70W-DL-B is available in several mounting configurations including ceiling mounting, pendant mounting, wall mounting and cable mounting.

Note on Beam Spread: The 360° beam spread is the standard directional output and typical for flood lights. The 180° shines in only one direction. This is good for down lighting, wall packs and for not blinding oncoming traffic or pedestrians.

Mounting Option Notes:

Pendant mounting option requires conduit be supplied by the installer.





Wall mounting option comes with Fixture Hanger.

High Quality Features

1. Low power consumption.
2. Instant on/off operation.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Superior color rendering compared to HPS, LPS, MV.
5. Retains 70% lumen output after 100,000 operating hours.
6. Powder coated aluminum fixture body.
7. Multiple Mounting Options Including Pendant, Wall, Ceiling, Cable Mounting and Swivel Bracket.
8. Low profile - Light weight
9. 6,000 Lumen output from only 70 watts

Superior LED Benefits

1. 100,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LARSON ELECTRONICS LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF LARSON ELECTRONICS LLC IS PROHIBITED.

DIMENSIONS ARE IN INCHES		NAME	
MATERIAL		DRAWN	CHRIS THAUER
		CHECKED	JEREMY BLANKENSHIP
DO NOT SCALE DRAWING			

TITLE:			
EPL-WPLED-70W-DL-B			
SIZE	DWG. NO.	REV	
A			
SCALE: 1:5		SHEET 1 OF 1	


5

4

3

2

1







Frequently Asked Questions (FAQ)