

Job #: J34459-2

Line-in Cord: N/A

Line-In Cord Cap: 400A Single-pole 16-Series Male Camlock Receptacles (2) Brown, (2) Orange, (2) Yellow, (1) Green [600V] with N3R Flip Covers

Primary Voltage (V): 480V AC Delta

Primary Phase (PH): 3-Phase (3PH)

Primary Frequency (HZ): 60 Hz (60-cycles)

Primary Panel: 480D 3PH 800A MCCB N3R

Primary Breakers: (12) 100A 3P MCCB [480V]; (6) 60A 3P MCCB [480V]

Primary Outlets: (6) 4100R7W IEC 60309 Pin & Sleeve Plug [480V]; (6) 460R7W IEC 60309 Pin & Sleeve Plug [480V]

Primary Protection: MCCB Circuit Breakers; Weather-proof Covers

Transformer (KVA): N/A

Secondary Voltage (V): N/A

Secondary Phase (PH): N/A

Secondary Frequency (HZ): N/A

Secondary Panel: N/A

Secondary Breakers: N/A

Secondary Outlets: N/A

Secondary Protection: N/A

Form Factor: Vertical Panel w/ 2" x 2" exterior frame cube, locking hinged door panel w/ key lock, Heavy Duty Caster Wheels, Bottom Forklift Skid Pockets, and 4-Corner Eyelet Picking Hook Holes

Max Primary OCP: 800A @ 480V

Max Secondary Output: N/A

Order notes: